


Throttle Valves



SR		G	06	10	
SERIES NUMBER		MOUNTING G : SUB-PLATE MOUNTING T : THREADED CONNECTIONS	VALVE SIZE 03 : 3/8" 06 : 3/4" 10 : 1-1/4"	DESIGN NUMBER	
Model		Max. Operated Pressure (kgf/cm ²)	Max. Flow (l/min)	Weight (kg)	
SUB-PLATE MOUNTING	THREADED CONNECTIONS				
SRG-03-10	SRT-03-10	250	30	1.4	1.1
SRG-06-10	SRT-06-10		80	2.4	2.8
SRG-10-10	SRT-10-10		200	5	6.1


Throttle and Check Valve



SRC		G	06	10	
SERIES NUMBER		MOUNTING G : SUB-PLATE MOUNTING T : THREADED CONNECTIONS	VALVE SIZE 03 : 3/8" 04 : 1/2" 06 : 3/4" 10 : 1-1/4"	DESIGN NUMBER	

Model		Max.Operated Pressure (kgf/cm ²)	Rated Flow (l/min)	Weight (kg)	
SUB-PLATE MOUNTING	THREADED CONNECTIONS				
SRCG-03-10	SRCT-03-10	250	30	2.3	1.5
SRCT-04-10			50	1.5	
SRCG-06-10	SRCT-06-10		80	4.3	3.8
SRCG-10-10	SRCT-10-10		200	8.6	7.3

Deceleration Throttle Valves



ZC	T	06	C	10
SERIES NUMBER	MOUNTING T : THREADED CONNECTIONS	VALVE SIZE 03 : 3/8" 06 : 3/4"	VALVE TYPE B : NORMALLY OPEN C : NORMALLY CLOSED	DESIGN NUMBER
Model	Max. Operated Pressure (kgf/cm ²)	Dr Port Max. Back Pressure kgf/cm ²	Max. Flow (l/min)	Weight (kg)
ZCT-03-	150	10	30	4.9
ZCT-06-	250		80	6.1